

WEIGHT	CUSTOMER NO:	REMARK
		SECOMP

300±15mm

P1

P2

1, 2, 3, 4

NOTES:

1. PIN ASSIGNMENT SEE TO WIRE LIST.

2. ELECTRICAL TEST CONDITION:

(a).100%OPEN,SHORT & MISWIRE TEST,

(b). INSULATOR RESISTANCE:10 Mohm MIN.

DC 300V 0.01sec.

(c). CONTACT RESISTANCE:3ohm MAX.

4	OVERMOLD BLACK PVC 45P MA-001.	
3	TERMINAL BLOCK GREEN 8PIN.	
2	8P8C PLUG WITH NICKLE PLATED SHELL.	
1	CAT.5e FTP 4P 24AWG STR OD:6.00mm L:300mm BLACK PVC JACKET	
NO.	Description	P/N

PIN ASSIGNMENT

P1		P2
1	8	1
2	8	2
3		3
6	8	6
4		4
5	8	5
7	8	7
8	8	8
S		

A		FIRST EDITION	BAO	2024/07/09
REV.	ECR	DESCRIPTION	C.N.	DATE
		SECOMP		
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°		TITLE ROLINE RJ45 M- Push-Terminal Block Connector Cable Adapter		
DIMENSIONS		TOLERANCE		CHKD.
0.00 TO 30.00mm		±0.10mm		CONF.
30.01 TO 80.00mm		±0.13mm		DR.
80.01 TO 150.00mm		±0.15mm		BAO
150.01mm		±0.20mm		APPD.
MATERIAL		MODEL NO:		12.02.1171
FINISH		SCALE		SHEET 1 / 1
		UNIT		MM
		SIZE		A4
		REV.		A