

		WEIGHT	CUSTOMER NO:	REMARK
				SECOMP

150±10mm

24±1

19

6.75±0.2

11.1

A1

B12

A12

B1

6.6

6.5

②③④

Type CM(Nickel plated)
Black Molding,NO:1963
TOL:±0.5mm

PIN ASSIGNMENT:

Type CM

A4+B4+A9+B9 ————— 1(+) Red

A7 ————— 2(D-)

A6 ————— 3(D+)

Shell+A1+B1+A12+B12 ————— 4(-) Black

————— 5(S) D

OPEN/SHORT TEST: 100% TEST.
INSULATION: 5M.

③④⑤

34.2

6

17

22.5

Black Radium vulture

5P Terminal block: PH=2.54mm
Black molding,NO:2183
TOL:±0.5mm

⑤	5P Terminal block: KF141V-2.54-5P, PH=2.54mm	1PCS
④	PE	5g
③	Black 45P PVC	10g
②	Type CM(Black Insulator,Nickel Plated),2.0,4PIN,5.1K,No Capacitance	1PCS
①	UL2725 28#*1P+24#*2C+AL+D+B(16*3/0.12AM) OD=4.5mm Black PVC Jacket	1PCS
No.	Description	Q'ty

A	REV.	ECR	FIRST EDITION	DESCRIPTION	BAO	C.N.	2024/07/09	DATE
SECOMP								
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°		TITLE TYPE C M- 5pin Push BUTTON Teminal Cable Adapter						
DIMENSIONS		TOLERANCE		CHKD.		CONF.		
0.00 TO 30.00mm		±0.10mm						
30.01 TO 80.00mm		±0.13mm						
80.01 TO 150.00mm		±0.15mm						
150.01mm		±0.20mm		DR. BAO		APPD.		
MATERIAL		MATERIAL		MODEL NO:		12.02.1173		
FINISH		FINISH		SCALE		SHEET 1 / 1		UNIT MM
						SIZE A4		REV. A