

Datenblatt Art. 392.180

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

Kabeltrommel 4-fach

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung	25m H05VV-F 3G1,5mm ²	Supply cable	25m H05VV-F 3G1,5mm ²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Stecker	CEE 7/7 (Type E/F)	Plug	CEE 7/7 (Type E/F)
Stromausgang		Power output	
Steckdosen		Socket outlets	
4x CEE 7/3 (Type F)		4x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Schwarz, ähnlich RAL 9005, 35°		Black, similar to RAL 9005, 35°	
16A / 250V~, IP20		16A / 250V~, IP20	
Schutzeinrichtungen		Protective devices	
Thermoschutzschalter	1-polig, rückstellbar	Thermo protection switch	1-pole, resettable
Weitere Produkteigenschaften		Further product attributes	
Durchmesser	285mm	Diameter	285mm
Material	Gehäuse: hochbruchfester Spezialkunststoff, schwarz	Material	Housing: unbreakable special plastic, black
Lieferumfang	1x Kabeltrommel 4-fach ohne Deckel	Scope of delivery	1x Cable reel 4-way without lid
Im Karton		In carton	
Umgebungsbedingungen		Environmental conditions	
Schutzart	IP20	Protection type	IP20
Konformität / Approbation		Conformity / Approval	

Bauart geprüft

DIN VDE 0620-1/
Bauart DIN 49440

Type approved

DIN VDE 0620-1/
Bauart DIN 49440

