


PIN OUT



CN1 (568B)		CN2 (568B)	
WHITE-ORANGE	1	1	WHITE-ORANGE
ORANGE	2	2	ORANGE
WHITE-GREEN	3	3	WHITE-GREEN
GREEN	6	6	GREEN
BLUE	4	4	BLUE
WHITE-BLUE	5	5	WHITE-BLUE
WHITE-BROWN	7	7	WHITE-BROWN
BROWN	8	8	BROWN
SHELL		DRAIN	SHELL

NOTE:

1. ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
2. FLUKE Channel TEST:
TEST LIMIT:ISO11801 Channel Class EA
3. Working temperature:-20°C~+75°C
Storage temperature:-20°C~+80°C
4. RoHS AND REACH compliant
5. Spray WORD:CAT6A U/FTP 4x2x32AWG/7 RECYCLED TPE ISO11801 & EN50173 & ANSI/TIA568. 2-D
6. Minimum of the bending radius is 4*OD (Suitable for all meters)

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK
③	OVER MOLD	RECYCLED PVC GREEN PANTONE 3278C	2	
②	PLUG	RJ45 8P8C SHIELDED PLUG, PIN GOLD PLATED 3U", THE SHELL PLATED NICKEL, COLOUR:TRANSPARENT GREEN	2	
①	CABLE	CAT. 6A U/FTP CABLE (32AWG BC+RECYCLED INSULATION*1P+AL-FOIL)*4+DRAIN JACKET:RECYCLED TPE GREEN PANTONE 3278C OD:3. 8±0. 2MM	1	
		NEW	2023-11-30	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

ITEM NO.	DESC.	LENGTH (mm)	The proportion of RECYCLED certification materials
21. 45. 3337	ROLINE RECYCLED U/FTP PatchCord Cat6A/C1.EA, SLIM, green, 5m	5000±100	61.60%
21. 45. 3336	ROLINE RECYCLED U/FTP PatchCord Cat6A/C1.EA, SLIM, green, 3m	3000±50	60.70%
21. 45. 3335	ROLINE RECYCLED U/FTP PatchCord Cat6A/C1.EA, SLIM, green, 2m	2000±30	59.70%
21. 45. 3334	ROLINE RECYCLED U/FTP PatchCord Cat6A/C1.EA, SLIM, green, 1.5m	1500±30	58.80%
21. 45. 3333	ROLINE RECYCLED U/FTP PatchCord Cat6A/C1.EA, SLIM, green, 1m	1000±20	57.40%
21. 45. 3332	ROLINE RECYCLED U/FTP PatchCord Cat6A/C1.EA, SLIM, green, 0.5m	500±20	54.70%
21. 45. 3331	ROLINE RECYCLED U/FTP PatchCord Cat6A/C1.EA, SLIM, green, 0.3m	300±10	52.80%
21. 45. 3330	ROLINE RECYCLED U/FTP PatchCord Cat6A/C1.EA, SLIM, green, 0.15m	150±10	50.70%

