



MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION
①	CABLE	UTP [24AWG 7*0.19±0.015mm((Bare Copper)*1PR)*4+PVC OD:5.8±0.3mm COLOR:RED
②	RJ45 CONNECTOR	RJ45,8P8C,TWO FORK GOLD PLATED CONTACTS
③	MOLDING	MOLDING PVC , COLOR:RED

(1)Jacket Color:Red(RAL 3000)

(2)wiring:T568B

Item No.	Length (M)	Tolerance(MM)
21.99.1420	0.5	+20/-10
21.99.1421	1	+/-20
21.99.1422	2	+/-40
21.99.1423	3	+/-60
21.99.1425	5	+/-110
21.99.1426	7	+/-140
21.99.1427	10	+/-200
21.99.1428	15	+/-310
21.99.1429	20	+/-400

Marking: E213738 CM (UL) C(UL) UTP PATCH CORD 24AWG 4P ISO/IEC 11801 AND TIA/EIA 568 CAT6A

ELECTRONIC TEST:

- A. OPEN/SHORT: 100%.
- B. WORKING TEMPERATURES:-20~60°C
- C. Minimum Banding Radius: 46MM

Item No.	21.99.1420	21.99.1421	21.99.1422	21.99.1423	21.99.1425
	21.99.1426	21.99.1427	21.99.1428	21.99.1429	
REMARK: NO	CHA NO	DESC	VALUE UTP Cat. 6a Patch Cord, red		
DRAWN BY	WEIHAIYAN		SECOMP		
APPROVED BY	MORGAN				
DATE	2015.09.22				