




24568-447 EUROPACPRO SIDE PANEL FOR TEXTILE GASKET, TYPE R, 6 U, 235  $\operatorname{\mathsf{MM}}$ 

















### **KEY FEATURES**

For high mechanical loads up to 25 g (vibration resistance, shock and vibration requirements e.g. IEC 61587-DL 3)

For high mechanical demands, 19" bracket 3,5mm and side panel 3mm, tox-cold welded together, clear passivated, front anodized

EMC shielding concept for front/rear with EMC textile gasket

Four mounting holes per 19" bracket provide improved stability when screwing the subrack into a cabinet or open frame rack

With holes for handle

## **PRODUCT ATTRIBUTES**

Product Type: Side Panel
Product Family: EuropacPRO
Type: Type R
Rack Height: 6 U
Board Depth: 235 mm
Package Quantity: 1
Package Unit: Pair
Depth: 235 mm

# ADDITIONAL PRODUCT DETAILS

Side Panel, Type R, tox welded to the 19" bracket for textile gasket, with handle holes and four fixing holes per 19" bracket.

Please order front handle separately.

Other dimensions on request.

Please order screws for mounting horizontal rails and top cover/base plate separately.



#### **North America**

All locations +1.763.422.2661 Chat with us: schroff.nvent.com

#### Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: schroff.nvent.com

nVent.com

### Asia

Shanghai, China +86.21.2412.6943 Qingdao, China +86.532.8771.6101 Singapore +65.6768.5800 Shin-Yokohama, Japan +81.45.476.0271 Chat with us: schroff.nvent.com

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

#### Middle East & India

Dubai, United Arab Emirates +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: schroff.nvent.com



© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

Our powerful portfolio of brands:

nVent reserves the right to change specifications without notice.