

21630-518 VARISTAR CP STAHLTÜR, PERFORIERT MIT 1-PUNKT-  
VERRIEGELUNG, NUR SCHLÜSSELSCHILD, RAL 7021. 47 HE, 2200 H, 800 B



**KEY FEATURES**

Perforierte Stahltür mit Einpunktverriegelung für IP-20-Schutzklasse.

Öffnungswinkel 180°

Schlüsselschild

**PRODUKTMERKMALE**

Produkttyp: Schranktür

Produktfamilie: Varistar CP

Typ: Stahltür, perforiert

Passend zu: Varistar CP

Verschlussstyp: Einzel-Punkt-Verriegelung

Material: Stahl

Farbe: Schwarzgrau

Farbecode: RAL 7021

Höhe: 47 HE

Höhe: 2200 mm

Breite (mm): 800 mm

Schutzart: IP20

Spezifikation: IEC 61587-1

## ZUSÄTZLICHE PRODUKTDDETAILS

---

Perforierte Varistar CP-Stahltür, IP 20 mit 1-Punkt-Verriegelung.

24 HE - 33 HE IP20 Türen haben 2 Scharniere, 38 HE - 52 HE IP20 Türen haben 3 Scharniere, um robuste IP20 Schließstrukturen für größere Schränke zu gewährleisten

Bitte bestellen Sie den Hebelgriff 24630003 und das DIN-Schloss separat, wenn Sie den Hebelgriff des 1333-DIN-Schlusses ersetzen möchten.

Bitte bestellen Sie den Erdungssatz separat.

### Nordamerika

All locations  
+1.763.422.2661  
Chat with us:  
[schroff.nvent.com](https://schroff.nvent.com)

### Europa

Straubenhardt, Deutschland  
+49.7082.794.0  
Betschdorf, Frankreich  
+33.3.88.90.64.90  
Warsaw, Poland  
+48.22.209.98.35  
Assago, Italy  
+39.02.932.7141  
Chat with us:  
[schroff.nvent.com](https://schroff.nvent.com)

### Asia

Shanghai, China  
+86.21.2412.6943  
Qingdao, Volksrepublik  
China  
+86.532.8771.6101  
Singapur  
+65.6768.5800  
Shin-Yokohama, Japan  
+81.45.476.0271  
Chat with us:  
[schroff.nvent.com](https://schroff.nvent.com)

### Middle East & India

Dubai, United Arab Emirates  
+971.4.378.1700  
Bangalore, Indien  
+91.80.6715.2001  
Istanbul, Turkey  
+90.216.250.7374  
Chat with us:  
[schroff.nvent.com](https://schroff.nvent.com)



Our powerful portfolio of brands:  
[nVent.com](https://nVent.com) **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.