


SJT3x14AWG
schwarz, mit angegossenem Schuko-USA Stecker, 15A
black, with moulded Schuko-USA plug, 15A
noir, avec prise moulée, Schuko-USA, 15A



* Endstücke geschraubt * Endcaps screwed * Embouts alambique

15 USA - Steckdosen	15 USA - sockets	15 prises USA
Steckdosen: <ul style="list-style-type: none"> Nema 5-15 2-polig mit Schutzkontakt; 15A, AC125V, IP20, Farbe: RAL7035 	Sockets: <ul style="list-style-type: none"> Nema 5-15 2-pole with earthing contact; 15A, AC125V, IP20, Colour: RAL7035; 	Prises: <ul style="list-style-type: none"> Nema 5-15 2 pôles, 1 prise de terre 15A, AC125V, IP20, RAL7035,
Anschluss: <ul style="list-style-type: none"> nicht wiederanschließbar; 	Connection: <ul style="list-style-type: none"> non rewirable, 	Connection: <ul style="list-style-type: none"> Reconnection impossible
Profil: 1HE, ALU, eloxiert;	Body: 1HE, ALU, anodized	Profilé: 1U, ALU, anodisé
Kunststoff: <ul style="list-style-type: none"> RAL7035, PA6, Glasfaser 30%, Glühdrahtprüfung bis 850°C; V1 	Plastic parts: <ul style="list-style-type: none"> RAL7035, PA6, fibre glass 30%, Glow wire test up to 850°C ; V1 	Éléments plastiques: <ul style="list-style-type: none"> RAL7035, PA6, fibre de verre 30%, test au fil incandescent : jusqu'à 850°C ; V1
Haltewinkel: <ul style="list-style-type: none"> Separat erhältlich: Artikelnr. 20110-068 	Brackets: <ul style="list-style-type: none"> Optional available, item no. 20110-068 	Equerres: <ul style="list-style-type: none"> à comander séparément, réf. 20110-068
Lieferform: <ul style="list-style-type: none"> Neutrale Kartonverpackung mit Schroff Art.-Nr. und Barcode 39 	Form of delivery: <ul style="list-style-type: none"> Neutral carton box With Schroff Item no. and bar code 39 	Conditionnement : <ul style="list-style-type: none"> Emballage dans carton neutre Avec réf. Schroff et code barre 39
Lieferumfang: <ul style="list-style-type: none"> 1 x Steckdosenleiste 	Extent of delivery: <ul style="list-style-type: none"> 1 x Socket strip 	Composition : <ul style="list-style-type: none"> 1 x Bâti de prises
Thermische Eigenschaften <ul style="list-style-type: none"> Betriebs- Umgebungstemperatur 0 ... +55°C Lagertemperatur -20... +75°C Betriebs-Umgebungsfeuchte 5... 95% nicht kondensierend 	Thermal specifications <ul style="list-style-type: none"> Operating temperature range 0...+55°C Storage temperature range -20... +75°C Operating humidity range 5...95% relative humidity, non-condensing 	Spécification thermiques <ul style="list-style-type: none"> Temperature de fonctionnement 0°+55° Temperature de stockage -20°... +75° Humidité en fonctionnement 5%... 95% sans condensation